

IMPORTANT!

READ ALL INSTRUCTIONS CAREFULLY

DO NOT DESTROY OR DISCARD ORIGINAL PACKING MATERIALS

It is imperative that you inspect your order as soon as your product has been received. CopperSmith cannot, under any circumstances, accept returns on products that have been installed. If a product arrives damaged, please save all original packing materials. Please photograph immediately and email the images to support@worldcoppersmith.com.

Disclaimer

Installation must be performed by a licensed professional only.

Installation must comply with all local building and safety codes.

Installation should not be scheduled until the product is received and inspected for damage or defect.

CopperSmith is not responsible for any installation delays or damages incurred as a result of installation.

CopperSmith is not responsible and does not supply any hardware or tools necessary for installation.

Guidelines

CopperSmith sinks should be installed according to all plumbing and building codes by a licensed contractor.

PLAN AHEAD - Because CopperSmith sinks are constructed from solid, heavy-gauge metals; they are considerably heavy. When unpacking your sink, make sure to place protective material (cardboard, packing foam, a throw rug, etc.) between your sink and the floor to avoid any damage. You may also need some assistance when moving or lifting your sink to avoid risk of personal injury.

Because CopperSmith products are hand-made, the specified dimensions of your sink may be approximate (+/- 1/8 inch). It is always best to use the actual basin of your sink as a template for any cutout requirements.

Make sure all drain connections have a secure, water-tight seal.

Always use non-water based, 100% silicone adhesive.

Make sure to leave enough space behind the basin for your back-splash, faucet, faucet handles, and any other accessories. Also make sure to accommodate a full range of motion for any moving parts.

CLEANUP - When cleaning up after the installation, DO NOT use abrasive cleaners or scouring materials that might damage or alter the sink's finish. Instead, use warm water and a soft cloth with a non-abrasive soap, such as dish soap.

Drop-in Sink Instructions

1. Lower the sink into the sink cut-out in the counter to confirm the sink will fit properly. The perimeter of the sink rim should connect with the counter while the sink bowl should sit completely inside the counter.
2. Remove the sink and run a bead of silicone sealant around the sink cut-out to seal the rim against moisture and leaks.
3. Carefully lower the sink back into the cut-out and press the sink firmly into the sealant. Make sure the sink is level and properly aligned.
4. If the sink is large and requires additional support, use 1/4" wood bracing under the 2" rim so the sink is fully supported.
5. Wipe away any excess sealant around the rim of the sink with a damp cloth.

